



Product Service

Attestation of Conformity

No. N8A 086470 0033 Rev. 02

Holder of Certificate: **Ginlong Technologies Co., Ltd.**
No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter**
Hybrid Inverter

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 704091623701-02

Date, 2020-08-03

(Zhengdong Ma)

Page 1 of 4

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 086470 0033 Rev. 02

Model(s): RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS, RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS, RHI-4.6K-48ES, RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS, RHI-5K-48ES, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS, RHI-6K-48ES, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS.

Parameters:

PV inputs:	
Max. input voltage	d.c. 600V
MPP voltage range	d.c. 90-520V
Max. input current	d.c. 2x11A
Isc PV (absolute maximum)	d.c. 2x17.2A
Battery:	
Battery type	Li-ion(RHI-3K-48ES, RHI-3.6K-48ES, RHI-4.6K-48ES, RHI-5K-48ES, RHI-6K-48ES), Li-ion/Lead-acid(RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS, RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
Battery voltage range	d.c. 42-58V
Max. charge/discharge current	d.c. 62.5A/62.5A (RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS, RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS, RHI-4.6K-48ES, RHI-5K-48ES, RHI-6K-48ES), d.c. 100A/100A (RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)



Attestation of Conformity

No. N8A 086470 0033 Rev. 02

AC-output (grid side):	
Rated output voltage	a.c. 220/230V
Rated output frequency	50/60Hz
Rated output power	3000W (RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS), 3600W (RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS), 4600W (RHI-4.6K-48ES, RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS), 5000W (RHI-5K-48ES, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS) 6000W (RHI-6K-48ES, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
Max. apparent output power	3300VA (RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS), 4000VA (RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS), 4600VA (RHI-4.6K-48ES, RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS), 5500VA (RHI-5K-48ES, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS), 6000VA (RHI-6K-48ES, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
Max. output current	a.c. 15.7A (RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS), a.c. 17.3A (RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS), a.c. 23A (RHI-4.6K-48ES, RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS), a.c. 23.9A (RHI-5K-48ES, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS), a.c. 26.1A (RHI-6K-48ES, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
Displacement factor	-0.8...1...+0.8



Product Service

Attestation of Conformity

No. N8A 086470 0033 Rev. 02

AC-output (back-up):	
Rated output voltage	a.c. 220/230V
Rated output frequency	50/60Hz
Rated output power	3000W (RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS, RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS, RHI-4.6K-48ES, RHI-5K-48ES, RHI-6K-48ES), 5000W (RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
Rated output current	a.c. 13A (RHI-3K-48ES, RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS, RHI-3.6K-48ES, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS, RHI-4.6K-48ES, RHI-5K-48ES, RHI-6K-48ES), a.c. 22A (RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
AC-input	
Rated voltage	a.c. 220/230V
Rated output frequency	50/60Hz
Current (Maximum continuous)	a.c. 23.9A (RHI-3K-48ES, RHI-3.6K-48ES, RHI-4.6K-48ES, RHI-5K-48ES, RHI-6K-48ES), a.c. 26.1A (RHI-3K-48ES-5G, RHI-3K-48ES-5G-NS, RHI-3.6K-48ES-5G, RHI-3.6K-48ES-5G-NS, RHI-4K-48ES-5G-NS, RHI-4.6K-48ES-5G, RHI-4.6K-48ES-5G-NS, RHI-5K-48ES-5G, RHI-5K-48ES-5G-NS, RHI-6K-48ES-5G, RHI-6K-48ES-5G-NS)
Protection class:	I
Degree of protection:	IP65
Overvoltage category:	II (PV), III (MAINS)
Ambient temperature:	-25°C...+60°C
Inverter topology:	Non-isolated

Tested according to:

EN 62109-1:2010
EN 62109-2:2011

Page 4 of 4

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.