



Product Service

# Attestation of Conformity

No. E8A 086470 0084 Rev. 01

**Holder of Certificate:** **Ginlong Technologies Co., Ltd.**  
No.57 Jintong Road  
Binhai Industrial Park, Xiangshan  
315712 Ningbo, Zhejiang  
PEOPLE'S REPUBLIC OF CHINA

**Name of Object:** **Converter**  
**(Hybrid Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64772218003102

**Date,** 2022-03-07

( Tony Liu )

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



# Attestation of Conformity

No. E8A 086470 0084 Rev. 01

**Model(s):** S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX, S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX, S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX, S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX, S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX

**Trade name:** solis  


## Description of Object:

PV inputs:	
Max. input voltage	d.c. 600V
MPP voltage range	d.c. 90-520V
Max. input current	d.c. 2x15A
Isc PV (absolute maximum)	d.c. 2x22.5A
Battery	
Battery type	Li-ion
Battery voltage range	d.c. 42-58V
Max. charge/discharge current	d.c. 62.5A/62.5A(S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX, S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), 100A/100A(S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX, S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX, S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX)
AC-output (grid side)	
Rated output voltage	a.c. 230V
Rated output frequency	50/60 Hz
Rated output power	3000W (S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX), 3600W (S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), 4600W (S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX), 5000W (S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX), 6000W (S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX)
Max. apparent output power	3300VA (S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX), 4000VA (S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), 4600VA (S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX), 5500VA (S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX), 6000VA (S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX)
Max. output current:	a.c. 15.0A (S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX), a.c. 18.2A (S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), a.c. 21A (S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX), a.c. 25A (S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX), a.c. 27.3A (S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX)
Displacement factor:	-0.8...1...+0.8



Product Service

# Attestation of Conformity

No. E8A 086470 0084 Rev. 01

AC-output (back-up)	
Rated output voltage	a.c. 230V
Rated output frequency	50Hz
Rated output power	3000W (S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX), 3600W (S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), 5000W (S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX, S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX, S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX),
Rated output current	a.c. 13.1A (S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX), a.c. 15.7A (S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), a.c. 21.7A (S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX, S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX, S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX)
AC-input	
Rated output voltage	a.c. 230V
Rated output frequency	50Hz
Max output current	a.c. 22A (S5-EH1P3K-L-UN, S5-EH1P3K-L-UN-EX), a.c. 26A (S5-EH1P3.6K-L-UN, S5-EH1P3.6K-L-UN-EX), a.c. 34.5A (S5-EH1P4.6K-L-UN, S5-EH1P4.6K-L-UN-EX, S5-EH1P5K-L-UN, S5-EH1P5K-L-UN-EX, S5-EH1P6K-L-UN, S5-EH1P6K-L-UN-EX)
Protection class:	I
Degree of protection:	IP54
Overvoltage category:	II (PV), III (MAINS)
Ambient temperature:	-20°C...+60°C(INV), System based on battery spec.

## Tested according to:

EN IEC 61000-6-1:2019  
 EN IEC 61000-6-2:2019  
 EN IEC 61000-6-3:2021  
 EN IEC 61000-6-4:2019  
 EN 61000-3-12:2011  
 EN IEC 61000-3-11:2019  
 EN 55011:2016/A11:2020  
 EN 55011:2016/A2:2021

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.