



Product Service

CERTIFICATE

No. B 086470 0029 Rev. 01

Holder of Certificate: **Ginlong Technologies Co., Ltd.**

No.57 Jintong Road
Binhai Industrial Park, Xiangshan
315712 Ningbo, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product:

**Converter
Grid-Tied Inverter**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704091716002-03

Valid until: 2026-09-08

Date, 2021-09-10

(Zhengdong Ma)

CERTIFICATE

No. B 086470 0029 Rev. 01

Model(s): Solis-25K-LV, Solis-30K-LV, Solis-40K, Solis-50K, Solis-50K-HV, Solis-60K-HV, Solis-60K-4G

Parameters:

Max. input voltage:	See attachment
MPP voltage range:	See attachment
Max. input current:	See attachment
Isc PV (absolute maximum):	See attachment
Rated grid voltage	See attachment
Rated grid frequency	50/60Hz
Max. AC output active power:	See attachment
Max. AC output apparent power	See attachment
Max. continuous output current:	See attachment
Adjustable cos(Φ):	-0.8...1...+0.8
Protection class	I
Degree of protection	IP65
Overtoltage category	II(PV), III(MAINS)
Ambient temperature	-25 ... +60°C
Other ratings refer to attachments.	

Electrical ratings for various model:

Models	Solis-25K-LV	Solis-30K-LV	Solis-40K	Solis-50K
PV input ratings				
Max. input voltage:	d.c. 1100 V	d.c. 1100 V	d.c. 1100 V	d.c. 1100 V
MPP voltage range:	d.c. 200-850V	d.c. 200-850V	d.c. 200-1000V	d.c. 200-1000V
Max. input current:	d.c. 2×28.5A	d.c. 2×28.5A	d.c. 4×22A	d.c. 4×28.5A
Isc PV (absolute maximum):	d.c. 2×44.5A	d.c. 2×44.5A	d.c. 4×34.3A	d.c. 4×44.5A
AC output ratings				
Rated grid voltage:	3~ 220V	3~ 220V	3/N/PE~ 230/400V	3/N/PE~ 230/400V
Rated grid frequency:	50/60Hz			
Max. AC output active power:	25000W	30000W	44000W	55000W
Max. AC output apparent power:	25000VA	30000VA	44000VA	55000VA
Max. Continuous output current:	a.c. 65.6 A	a.c. 78.8 A	a.c. 66.9 A	a.c. 83.3 A

CERTIFICATE

No. B 086470 0029 Rev. 01

Models	Solis-50K-HV	Solis-60K-HV	Solis-60K-4G
PV input ratings			
Max. input voltage:	d.c. 1100 V	d.c. 1100 V	d.c. 1100 V
MPP voltage range:	d.c. 200-1000V	d.c. 200-1000V	d.c. 200-1000V
Max. input current:	d.c. 4×22A	d.c. 4×28.5A	d.c. 4×28.5A
Isc PV (absolute maximum):	d.c. 4×34.3A	d.c. 4×44.5A	d.c. 4×44.5A
AC output ratings			
Rated grid voltage:	3~ 480V	3~ 480V	3/N/PE~ 230/400V
Rated grid frequency:	50/60Hz		
Max. AC output active power:	55000W	66000W	66000W
Max. AC output apparent power:	55000VA	66000VA	66000VA
Max. Continuous output current:	a.c. 66.2 A	a.c. 80 A	a.c. 100 A

Tested according to: IEC 62109-1(ed.1)
 IEC 62109-2(ed.1)
 EN 62109-1:2010
 EN 62109-2:2011